

Syntpaper SY-P

Syntpaper SY-P is a high-density, biaxially oriented polypropylene (BOPP) film, supplied with a special coat application, enabling excellent print quality and sharp images. It is also prepared to receive special adhesives and glues – acrylic or dry – for heat sealing.

Printing

Offset
Flexography Thermal transfer (wax, mixed and resin ribbons)
Silkscreen
Rotogravure
Digital

Supply

Jumbo coil, cut-to-measure coil desired and sheets, with and without adhesive.

Applications

Packaging, luggage labels, banners, posters, promotional folders, labels.

Maximum temperature of use:

120°C degress

technical specifications

Syntpaper SY-P

SYNTPAPER SY-P WITH COAT					
Items	Unit	Results			
		80	120	150	180
Thickness	mm	0,080mm	0,12mm	0,15mm	0,18mm
Thickness Tolerance	%	5	5	5	5
Weight	g/m ²	68.8	93.6	114	131.4
Roughness		1.5	1.5	1.5	1.5
Brightness	%	13/14	13/15	14/14	14/14
Whiteness	%	92	92	92	92
Opacity	%	87	90	92	93
Surface resistance	--	10 ¹²			
Specific gravity	--	0.86	0.78	0.76	0.73

Important:

The above information is derived from quality testing for reference only. The buyer must verify that the product is suitable for its intended use before starting the manufacturing or conversion process.

Expiration Date of the Product:

1 year after the invoice date.

Contact

phone [+ 55 11] 4161 8800
email marketing@syntpaper.com.br

www.syntpaper.com.br

SYNTPAPER
SYP

SYNTPAPER
SYP